



MATERIAL PNEUROP KF

MATERIAL PNEUROP KF

KF Flange system

KF is a simple, flexible "O" ring vacuum flange system available up to 50 mm. It is also well known as NW system.

The KF or NW system is defined by Pneurop 6606 (1981), ISO 1609 (1986) and DIN 28403.

All VCS components are interchangeable with all assemblies made in complain to above standard; all welded assembly is helium leak checked and can be certified to have a leak rate of less than $1 \cdot 10^{-9}$ mbar $\cdot$ l/s.

An assembly consists of two identical sexless, 360° rotatable, smooth-faced flanges, a quick acting enclosing rim-clamp and a center ring which support an elastomer "O"ring to align the flanges and prevent the "O"ring from collapsing. The quick acting clamp compresses the self-centering, sealing ring between the two flanges.

The KF sealing mechanism works from atmosphere to the low 10⁻⁷ mbar, within the temperature range -20°C. to 200°C. depending


on the construction and "O" ring material. Lower pressure (10⁻⁸ mbar) can be reached in systems where Viton "O"rings are baked to 180°C.

Stainless steel flanged components are used for high temperature and corrosion conditions and aluminium or brass for more general applications.

Clamps are made from polymeric materials, cast aluminium, machined aluminium, and stainless steel, with two or three hinged segments and a variety of closing mechanism including thumbscrews, over-center levers, threaded rods or nuts, or set screw. The most popular are either of the first two since no tools are required.

The common elastomer "O"ring used in KF flanges are, depending on temperature and the composition of the gas: Buna-N, fluorocarbon (as Viton A), and silicone rubber. Chemraz or Kalrez having the best high temperature performances can also be used but are very expensive.


Typical Operating Temperature	(extreme conditions)	
Buna-N	-20°C. to +80°C.	-40°C. to +120°C.
Viton A	-20°C. to +180°C.	-40°C. to +200°C.
Silicon	-30°C. to +200°C.	-40°C. to +300°C.





- 1 Small flange port
- 2 Housing panel with thread
- 3 Claw grip
- 4 Center ring


	A	B	C	D	Number of claw grips
DN 10 KF	30	12,2	12,2	45	4
DN 16 KF	30	17,2	17,2	45	4
DN 20 KF	40	22,2	22,2	55	4
DN 25 KF	40	26,2	26,2	55	4
DN 32 KF	55	34,2	34,2	71	4
DN 40 KF	55	41,2	41,2	71	4
DN 50 KF	75	52,2	52,2	91	4


Small flange components to DIN 28043 or Pneurop 6606 standard

		Nominal diameter	A	B	C	D	Order n°
Clamping ring							
Aluminium							
		DN 10-16 KF	43	22	16	62	VP-A01-016
		DN 20-25 KF	55	32	16	72	VP-A01-025
		DN 32-40 KF	70	47	16	90	VP-A01-040
		DN 50 KF	95	63	25	123	VP-A01-050


Clamping ring for metal seal							
Stainless Steel							
		DN 10-16 KF	54	22	18		VP-A02-016
		DN 20-25 KF	64	32	18		VP-A02-025
		DN 32-40 KF	82	47	18		VP-A02-040
		DN 50 KF	112	62	18		VP-A02-050

Isolated clamping ring							
Zelamit							
		DN 10-16 KF	54	22	18		VP-A03-016
		DN 20-25 KF	64	32	18		VP-A03-025
		DN 32-40 KF	82	47	18		VP-A03-040
		DN 50 KF	112	62	18		VP-A03-050


Claw grip							
Stainless Steel							
		DN 10-50 KF	20	12	14	20	VP-A04-000

		Nominal diameter	A	B	C	D	Order n°	
Centering ring								
		Stainless Steel-Viton	DN 10 KF	12	10	8	3,9	VP-A05-010
			DN 16 KF	17	16	8	3,9	VP-A05-016
			DN 25 KF	26	25	8	3,9	VP-A05-025
			DN 40 KF	41	40	8	3,9	VP-A05-040
			DN 50 KF	52	50	8	3,9	VP-A05-050
Stainless Steel-NBR		DN 10 KF	12	10	8	3,9	VP-A05-110	
		DN 16 KF	17	16	8	3,9	VP-A05-116	
		DN 25 KF	26	25	8	3,9	VP-A05-125	
		DN 40 KF	41	40	8	3,9	VP-A05-140	
		DN 50 KF	52	50	8	3,9	VP-A05-150	
Aluminium-Viton		DN 10 KF	12	10	8	3,9	VP-A05-210	
		DN 16 KF	17	16	8	3,9	VP-A05-216	
		DN 25 KF	26	25	8	3,9	VP-A05-225	
		DN 40 KF	41	40	8	3,9	VP-A05-240	
		DN 50 KF	52	50	8	3,9	VP-A05-250	
Aluminium-NBR		DN 10 KF	12	10	8	3,9	VP-A05-310	
		DN 16 KF	17	16	8	3,9	VP-A05-316	
		DN 25 KF	26	25	8	3,9	VP-A05-325	
		DN 40 KF	41	40	8	3,9	VP-A05-340	
		DN 50 KF	52	50	8	3,9	VP-A05-350	
Teflon-Viton		DN 10 KF	12	10	8	3,9	VP-A05-410	
		DN 16 KF	17	16	8	3,9	VP-A05-416	
		DN 25 KF	26	25	8	3,9	VP-A05-425	
		DN 40 KF	41	40	8	3,9	VP-A05-440	
		DN 50 KF	52	50	8	3,9	VP-A05-450	
Teflon-NBR		DN 10 KF	12	10	8	3,9	VP-A05-510	
		DN 16 KF	17	16	8	3,9	VP-A05-516	
		DN 25 KF	26	25	8	3,9	VP-A05-525	
		DN 40 KF	41	40	8	3,9	VP-A05-540	
		DN 50 KF	52	50	8	3,9	VP-A05-550	


O-Ring		Nominal diameter	A	B	C	D	Order n°
	Viton	DN 10 KF	15	5		5	VP-A06-010
		DN 16 KF	18	5		5	VP-A06-016
		DN 25 KF	28	5		5	VP-A06-025
		DN 40 KF	42	5		5	VP-A06-040
		DN 50 KF	52	5		5	VP-A06-050
	NBR	DN 10 KF	15	5		10	VP-A06-110
		DN 16 KF	18	5		10	VP-A06-116
		DN 25 KF	28	5		10	VP-A06-125
		DN 40 KF	42	5		10	VP-A06-140
		DN 50 KF	52	5		10	VP-A06-150
		D = quantity delivered					










External centering ring							
	Aluminium-Viton	DN 10-16 KF	30	32	7	3,9	VP-A07-016
		DN 20-25 KF	40	42	7	3,9	VP-A07-025
		DN 32-40 KF	55	57	7	3,9	VP-A07-040
		DN 50 KF	75	77	7	3,9	VP-A07-050












Centering ring with optical baffle							
	Stainless Steel-Viton	DN 16 KF	17	16	8	3,9	VP-A08-016
		DN 25 KF	26	25	8	3,9	VP-A08-025
		DN 40 KF	41	40	8	3,9	VP-A08-040









		Nominal diameter	A	B	C	D	Order n°
Reducing centering ring							
Stainless Steel-Viton							
		DN 10-16 KF	17	10	12		VP-A09-016
		DN 20-25 KF	26	21	22		VP-A09-025
		DN 32-40 KF	41	32	34		VP-A09-040
Stainless Steel-NBR							
		DN 10-16 KF	17	10	12		VP-A09-116
		DN 20-25 KF	26	21	22		VP-A09-125
		DN 32-40 KF	41	32	34		VP-A09-140
Metal seal							
Aluminium							
		DN 10-16 KF	30	32	7	2	VP-A10-016
		DN 20-25 KF	40	42	7	2	VP-A10-025
		DN 32-40 KF	55	57	7	2	VP-A10-040
		DN 50 KF	75	77	7	2	VP-A10-050
Centering ring with sintered metal filter							
Stainless Steel-Viton							
		DN 16 KF	17	14	8	3,9	VP-A11-016
		DN 25 KF	26	23	8	3,9	VP-A11-025
		DN 40 KF	41	38	8	3,9	VP-A11-040






		Nominal diameter	A	B	C	D	Order n°
Blanking flange							
Stainless Steel 		DN 10 KF	30	5			VP-A12-010
		DN 16 KF	30	5			VP-A12-016
		DN 25 KF	40	5			VP-A12-025
		DN 40 KF	55	5			VP-A12-040
		DN 50 KF	75	5			VP-A12-050
Aluminium		DN 10 KF	30	5			VP-A12-110
		DN 16 KF	30	5			VP-A12-116
		DN 25 KF	40	5			VP-A12-125
		DN 40 KF	55	5			VP-A12-140
		DN 50 KF	75	5			VP-A12-150
Weld flange							
Stainless Steel 		DN 10 KF	30	14	10	3,5	VP-A13-010
		DN 16 KF	30	20	16	3,5	VP-A13-016
		DN 25 KF	40	28	24	3,5	VP-A13-025
		DN 40 KF	55	45	41	3,5	VP-A13-040
		DN 50 KF	75	57	50	3,5	VP-A13-050
Short weld flange							
Stainless Steel 		DN 10 KF	30	14	10		VP-A14-010
		DN 16 KF	30	20	16		VP-A14-016
		DN 25 KF	30	28	24		VP-A14-025
		DN 40 KF	30	45	41		VP-A14-040
		DN 50 KF	30	57	50		VP-A14-050
Long weld flange							
Stainless Steel 		DN 10 KF	70	14	10		VP-A15-010
		DN 16 KF	70	20	16		VP-A15-016
		DN 25 KF	70	28	24		VP-A15-025
		DN 40 KF	70	45	41		VP-A15-040
		DN 50 KF	70	57	50		VP-A15-050

		Nominal diameter	A	B	C	D	Order n°
Intermediate piece							
Stainless Steel							
		DN 10 KF	60				VP-A16-010
		DN 16 KF	80				VP-A16-016
		DN 25 KF	100				VP-A16-025
		DN 40 KF	130				VP-A16-040
		DN 50 KF	140				VP-A16-050
Elbow 90°							
Stainless Steel							
		DN 10 KF	30				VP-A17-010
		DN 16 KF	40				VP-A17-016
		DN 25 KF	50				VP-A17-025
		DN 40 KF	65				VP-A17-040
		DN 50 KF	70				VP-A17-050
T-piece							
Stainless Steel							
		DN 10 KF	30	60			VP-A18-010
		DN 16 KF	40	80			VP-A18-016
		DN 25 KF	50	100			VP-A18-025
		DN 40 KF	65	130			VP-A18-040
		DN 50 KF	70	140			VP-A18-050
Cross-piece							
Stainless Steel							
		DN 10 KF	30	60			VP-A19-010
		DN 16 KF	40	80			VP-A19-016
		DN 25 KF	50	100			VP-A19-025
		DN 40 KF	65	130			VP-A19-040
		DN 50 KF	70	140			VP-A19-050
Double cross-piece							
Stainless Steel							
		DN 10 KF	30	60			VP-A20-010
		DN 16 KF	40	80			VP-A20-016
		DN 25 KF	50	100			VP-A20-025
		DN 40 KF	65	130			VP-A20-040
		DN 50 KF	70	140			VP-A20-050

		Nominal diameter	A	B	C	D	Order n°
Reducing T-piece							
Stainless Steel							
		DN 25-16 KF	50	100	40		VP-A21-125
		DN 40-16 KF	65	130	40		VP-A21-140
		DN 40-25 KF	65	130	50		VP-A21-240
		DN50-25 KF	70	140	50		VP-A21-250
		DN 50-40 KF	70	140	65		VP-A21-450
Reducing cross-piece							
Stainless Steel							
		DN 25-16 KF	50	100	40	80	VP-A22-125
		DN 40-16 KF	65	130	40	80	VP-A22-140
		DN 40-25 KF	65	130	50	100	VP-A22-240
		DN50-25 KF	70	140	50	100	VP-A22-250
		DN 50-40 KF	70	140	65	130	VP-A22-450
Reducing-piece							
Stainless Steel							
		DN 25-16 KF	28				VP-A23-125
		DN 40-16 KF	28				VP-A23-140
		DN 40-25 KF	28				VP-A23-240
		DN 50-25 KF	28				VP-A23-250
		DN 50-40 KF	28				VP-A23-450
Conical reducing-piece							
Stainless Steel							
		DN 25-16 KF	40				VP-A24-125
		DN 40-16 KF	40				VP-A24-140
		DN 40-25 KF	40				VP-A24-240

		Nominal diameter	A	B	C	D	Order n°
Screw-in flange							
Stainless Steel-Viton							
		DN 10 KF-G 3/8	35	15	G 3/8	10	VP-A35-010
		DN 16 KF-G1/2	35	16	G 1/2	16	VP-A35-016
		DN 25 KF-G 1	45	24	G 1	24	VP-A35-025
		DN 40 KF-G 1 1/2	50	28	G 1 1/2	40	VP-A35-040
Screw-on flange							
Stainless Steel-Viton							
		DN 10 KF-G 3/8	35	15	G 3/8	10	VP-A36-010
		DN 16 KF-G1/2	35	16	G 1/2	16	VP-A36-016
		DN 25 KF-G 1	45	24	G 1	24	VP-A36-025
		DN 40 KF-G 1 1/2	50	28	G 1 1/2	40	VP-A36-040
Hose nipple							
Stainless Steel							
		DN 16 KF	40	12	8		VP-A37-016
		DN 25 KF	40	12	8		VP-A37-025
		DN 40 KF	40	12	8		VP-A37-040

		Nominal diameter	A	B	C	D	Order n°
Flexible metal hose							
Stainless Steel							
		DN 10 KF	250				VP-A38-010
		DN 16 KF	250				VP-A38-016
		DN 25 KF	250				VP-A38-025
		DN 40 KF	250				VP-A38-040
		DN 50 KF	250				VP-A38-050
		DN 10 KF	500				VP-A38-110
		DN 16 KF	500				VP-A38-116
		DN 25 KF	500				VP-A38-125
		DN 40 KF	500				VP-A38-140
		DN 50 KF	500				VP-A38-150
		DN 10 KF	750				VP-A38-210
		DN 16 KF	750				VP-A38-216
		DN 25 KF	750				VP-A38-225
		DN 40 KF	750				VP-A38-240
		DN 50 KF	750				VP-A38-250
		DN 10 KF	1000				VP-A38-310
		DN 16 KF	1000				VP-A38-316
		DN 25 KF	1000				VP-A38-325
		DN 40 KF	1000				VP-A38-340
		DN 50 KF	1000				VP-A38-350
Bellow							
Stainless Steel							
		DN 10 KF	90	15			VP-A39-010
		DN 16 KF	120	22			VP-A39-016
		DN 25 KF	120	22			VP-A39-025
		DN 40 KF	120	22			VP-A39-040
		DN 50 KF	120	22			VP-A39-050
Braided flexible metal hose							
Stainless Steel							
		DN 16 KF	500				VP-A40-016
		DN 25 KF	500				VP-A40-025
		DN 40 KF	500				VP-A40-040
		DN 16 KF	1000				VP-A40-116
		DN 25 KF	1000				VP-A40-125
		DN 40 KF	1000				VP-A40-140

		Nominal diameter	A	B	C	D	Order n°
Flange for PVC hose							
Aluminium							
		DN 16 KF	30	18	15		VP-A41-016
		DN 25 KF	30	27	24		VP-A41-025
		DN 40 KF	30	43	39		VP-A41-040
PVC hose with steel spiral							
PVC							
		DN 16 KF	16	22,4			VP-A42-016
		DN 25 KF	25	33			VP-A42-025
		DN 40 KF	40	50			VP-A42-040
		Price for one metre					
PVC hose complete							
Aluminium-PVC							
		DN 16 KF	500				VP-A43-016
		DN 25 KF	500				VP-A43-025
		DN 40 KF	500				VP-A43-040
		DN 16 KF	1000				VP-A43-116
		DN 25 KF	1000				VP-A43-125
		DN 40 KF	1000				VP-A43-140
Viewport							
Plexiglass							
		DN 16 KF	30	10			VP-A44-016
		DN 25 KF	40	10			VP-A44-025
		DN 40 KF	55	10			VP-A44-040
Protective cover							
Plastic							
		DN 10-16 KF				10	VP-A45-016
		DN 20-25 KF				10	VP-A45-025
		DN 32-40 KF				10	VP-A45-040
		DN 50 KF				10	VP-A45-050
		D = quantity delivered					



MATERIAL PNEUROP ISO-K

MATERIAL PNEUROP ISO-K

ISO Flange system

The ISO flange, defined by ISO 1609 (1986) and DIN 28404, has the same principle as the NW flange with two basic type of smooth-faced sexless flanges, an "O"ring, a center ring and several fastening methods. Some of them are showed below.

Manufacturers of ISO components machine flanges with interface dimensions in complain to the standards and they are interchangeable. Fittings and adapters, however, have not international standards and they dimension change with manufacturers. All VCS components dimensions are shown in this catalogue. All welded assembly is helium leak checked and can be certified to have a leak rate of less than 1×10^{-9} mbar $\cdot$ l/s.


The ISO sealing mechanism are totally reliable in vacuum system from atmosphere to 10^{-6} mbar without baking and down to the

10 $\cdot$ 8 range, with Viton "O"ring baked up to 180°C.

In this system the clamping mechanism is either bolts through holes in flanges (ISO-F styles) or a number of individual clamps that are spaced around and hook over, the outer edge of the mating flanges (ISO-K) styles.


ISO-K flanges, sexless, infinitely rotatable, self-centering, are usually less expensive and better suited to restricted space with less clearance than is needed for the ISO-F.

ISO-F flanges, sexless, self-centering, are stronger and are preferred when vacuum piping is used as a structural element of the system. ISO-K flanges can be converted to an infinitely rotatable ISO-F by adding a bolt ring and a wire snap ring (rotatable kit).




Clamp flange component to DIN 28404 or Pneurop 6606 standard

	A	B	C	Number clamps
DN 63 ISO	95	70	12	4
DN 100 ISO	130	102	12	4
DN 160 ISO	180	153	12	4
DN 200 ISO	240	213	12	6
DIN 250 ISO	290	261	12	6
DN 320 ISO	370	318	17	8
DN 400 ISO	450	400	17	8
DN 500 ISO	550	501	17	12
DN 630 ISO	690	651	22	12









	D	E	Number of holes	Screws
DN 63 ISO	130	110	4	M8x40
DN 100 ISO	165	145	8	M8x40
DN 160 ISO	225	200	8	M10x50
DN 200 ISO	285	260	12	M10x50
DN 250 ISO	335	310	12	M10x50
DN 320 ISO	425	395	12	M12x60
DN 400 ISO	510	480	16	M12x60
DN 500 ISO	610	580	16	M12x60
DN 630 ISO	750	720	20	M12x70












	E	Screws	Number of claw grips
DN 63 ISO	110	M8x35	4
DN 100 ISO	145	M8x35	8
DN 160 ISO	200	M10x40	8
DN 200 ISO	260	M10x40	12
DN 250 ISO	310	M10x40	12
DN 320 ISO	395	M12x50	12
DN 400 ISO	480	M12x50	16
DN 500 ISO	580	M12x50	16
DN 630 ISO	720	M12x55	20



		Nominal diameter	A	B	C	D	Order n°
Claw clamp							
	Steel, zinc plated	DN 63-250 ISO	60	27	17		VP-B01-025
		DN320-500 ISO	75	39	27		VP-B01-050
		DN 630 ISO	85	46	30		VP-B01-063
	Stainless Steel	DN 63-250 ISO	60	27	17		VP-B01-125
		DN320-630 ISO	75	39	27		VP-B01-150
Claw grip for use with centering ring							
	Steel, zinc plated	DN 63-100 ISO	22,5	35	10		VP-B02-010
		DN 160-250 ISO	23	35	10		VP-B02-025
		DN320-500 ISO	36,5	50	15		VP-B02-050
	Stainless Steel	DN 63-100 ISO	22,5	35	10		VP-B02-110
		DN 160-250 ISO	23	35	10		VP-B02-125
		DN320-500 ISO	36,5	50	15		VP-B02-150
		DN 630 ISO	41,5	55	20		VP-B02-163
Claw grip for use with sealing groove							
	Steel, zinc plated	DN 63-100 ISO	18,6	30	10		VP-B03-010
		DN 160-250 ISO	19,1	35	10		VP-B03-025
		DN320-500 ISO	30,9	45	15		VP-B03-050
	Stainless Steel	DN 63-100 ISO	18,6	30	10		VP-B03-110
		DN 160-250 ISO	19,1	35	10		VP-B03-125
		DN320-500 ISO	30,9	45	15		VP-B03-150
		DN 630 ISO	36,5	55	20		VP-B03-163






		Nominal diameter	A	B	C	D	Order n°	
Centering ring								
		Stainless Steel - Viton	DN 63 ISO	70	67	8	3,9	VP-B04-006
		DN 100 ISO	102	99	8	3,9	VP-B04-010	
		DN 160 ISO	153	150	8	3,9	VP-B04-016	
		DN 200 ISO	213	210	8	3,9	VP-B04-020	
		DN 250 ISO	261	258	8	3,9	VP-B04-025	
		DN 320 ISO	318	313	14	5,6	VP-B04-032	
		DN 400 ISO	400	395	14	5,6	VP-B04-040	
		DN 500 ISO	501	495	14	5,6	VP-B04-050	
		DN 630 ISO	651	645	14	5,6	VP-B04-063	
Stainless Steel - NBR		DN 63 ISO	70	67	8	3,9	VP-B04-106	
		DN 100 ISO	102	99	8	3,9	VP-B04-110	
		DN 160 ISO	153	150	8	3,9	VP-B04-116	
		DN 200 ISO	213	210	8	3,9	VP-B04-120	
		DN 250 ISO	261	258	8	3,9	VP-B04-125	
Aluminium - Viton		DN 63 ISO	70	67	8	3,9	VP-B04-206	
		DN 100 ISO	102	99	8	3,9	VP-B04-210	
		DN 160 ISO	153	150	8	3,9	VP-B04-216	
		DN 200 ISO	213	210	8	3,9	VP-B04-220	
		DN 250 ISO	261	258	8	3,9	VP-B04-225	
		DN 320 ISO	318	313	14	5,6	VP-B04-232	
		DN 400 ISO	400	395	14	5,6	VP-B04-240	
		DN 500 ISO	501	495	14	5,6	VP-B04-250	
		DN 630 ISO	651	645	14	5,6	VP-B04-263	
Aluminium - NBR		DN 63 ISO	70	67	8	3,9	VP-B04-306	
		DN 100 ISO	102	99	8	3,9	VP-B04-310	
		DN 160 ISO	153	150	8	3,9	VP-B04-316	
		DN 200 ISO	213	210	8	3,9	VP-B04-320	
		DN 250 ISO	261	258	8	3,9	VP-B04-325	
Centering ring with aluminium outer ring								
		Stainless Steel - Viton	DN 63 ISO	95	70	8	3,9	VP-B05-006
		DN 100 ISO	128	102	8	3,9	VP-B05-010	
		DN 160 ISO	179	153	8	3,9	VP-B05-016	
		DN 200 ISO	238	213	8	3,9	VP-B05-020	
		DN 250 ISO	286	261	8	3,9	VP-B05-025	
Aluminium - Viton		DN 63 ISO	95	70	8	3,9	VP-B05-106	
		DN 100 ISO	128	102	8	3,9	VP-B05-110	
		DN 160 ISO	179	153	8	3,9	VP-B05-116	
		DN 200 ISO	238	213	8	3,9	VP-B05-120	
		DN 250 ISO	286	261	8	3,9	VP-B05-125	

		Nominal diameter	A	B	C	D	Order n°
Flange with pipe							
Stainless Steel							
		DN 63 ISO-K	100	76	70		VP-B15-006
		DN 100 ISO-K	100	108	102		VP-B15-010
		DN 160 ISO-K	100	159	153		VP-B15-016
		DN 200 ISO-K	100	219	213		VP-B15-020
		DN 250 ISO-K	100	267	261		VP-B15-025
		DN 320 ISO-K	100	324	318		VP-B15-032
		DN 400 ISO-K	100	408	400		VP-B15-040
		DN 500 ISO-K	100	508	500		VP-B15-050
		DN 630 ISO-K	100	660	650		VP-B15-063
Intermediate piece							
Stainless Steel							
		DN 63 ISO-K	100				VP-B16-006
		DN 100 ISO-K	100				VP-B16-010
		DN 160 ISO-K	100				VP-B16-016
		DN 200 ISO-K	100				VP-B16-020
		DN 250 ISO-K	100				VP-B16-025
Elbow 90°							
Stainless Steel							
		DN 63 ISO-K	88				VP-B17-006
		DN 100 ISO-K	108				VP-B17-010
		DN 160 ISO-K	138				VP-B17-016
		DN 200 ISO-K	178				VP-B17-020
		DN 250 ISO-K	208				VP-B17-025
T-piece							
Stainless Steel							
		DN 63 ISO-K	88	176			VP-B18-006
		DN 100 ISO-K	108	216			VP-B18-010
		DN 160 ISO-K	138	276			VP-B18-016
		DN 200 ISO-K	178	356			VP-B18-020
		DN 250 ISO-K	208	416			VP-B18-025

		Nominal diameter	A	B	C	D	Order n°
Cross-piece							
Stainless Steel							
		DN 63 ISO-K	88	176			VP-B19-006
		DN 100 ISO-K	108	216			VP-B19-010
		DN 160 ISO-K	138	276			VP-B19-016
		DN 200 ISO-K	178	356			VP-B19-020
		DN 250 ISO-K	208	416			VP-B19-025
Double cross-piece							
Stainless Steel							
		DN 63 ISO-K	88	176			VP-B20-006
		DN 100 ISO-K	108	216			VP-B20-010
		DN 160 ISO-K	138	276			VP-B20-016
		DN 200 ISO-K	178	356			VP-B20-020
		DN 250 ISO-K	208	416			VP-B20-025
Reducing T-piece							
Stainless Steel							
		DN 100-63 ISO-K	216	100			VP-B21-010
		DN 160-100 ISO-K	276	130			VP-B21-016
		DN 200-160 ISO-K	356	160			VP-B21-020
		DN 250-200 ISO-K	416	190			VP-B21-025
Reducing cross-piece							
Stainless Steel							
		DN 100-63 ISO-K	216	100			VP-B22-010
		DN 160-100 ISO-K	276	130			VP-B22-016
		DN 200-160 ISO-K	356	160			VP-B22-020
		DN 250-200 ISO-K	416	190			VP-B22-025

		Nominal diameter	A	B	C	D	Order n°
Reducing-piece ISO-K / ISO-K							
Stainless Steel							
		DN 100-63 ISO-K	50				VP-B23-010
		DN 160-100 ISO-K	50				VP-B23-016
		DN 200-160 ISO-K	50				VP-B23-020
		DN 250-200 ISO-K	50				VP-B23-025
Conical reducing-piece							
Stainless Steel							
		DN 100-63 ISO-K	100				VP-B24-010
		DN 160-100 ISO-K	120				VP-B24-016
		DN 200-160 ISO-K	140				VP-B24-020
		DN 250-200 ISO-K	160				VP-B24-025
Adaptor piece ISO-K / KF							
Stainless Steel							
		DN 63 ISO-K / 25 KF	40				VP-B25-062
		DN 63 ISO-K / 40 KF	40				VP-B25-064
		DN 100 ISO-K / 40 KF	40				VP-B25-104
		DN 100 ISO-K / 50 KF	40				VP-B25-105
		DN 160 ISO-K / 40 KF	40				VP-B25-164
Spherical cross-piece							
Stainless Steel							
		DN 63 ISO-K	88	176			VP-B30-006
		DN 100 ISO-K	108	216			VP-B30-010
		DN 160 ISO-K	138	276			VP-B30-016
		DN 200 ISO-K	178	356			VP-B30-020
		DN 250 ISO-K	208	416			VP-B30-025
Spherical double cross-piece							
Stainless Steel							
		DN 63 ISO-K	88	176			VP-B31-006
		DN 100 ISO-K	108	216			VP-B31-010
		DN 160 ISO-K	138	276			VP-B31-016
		DN 200 ISO-K	178	356			VP-B31-020
		DN 250 ISO-K	208	416			VP-B31-025

		Nominal diameter	A	B	C	D	Order n°
Flexible metal hose							
Stainless Steel							
		DN 63 ISO-K	250				VP-B38-006
		DN 100 ISO-K	250				VP-B38-010
		DN 160 ISO-K	250				VP-B38-016
		DN 63 ISO-K	500				VP-B38-106
		DN 100 ISO-K	500				VP-B38-110
		DN 160 ISO-K	500				VP-B38-116
		DN 63 ISO-K	750				VP-B38-206
		DN 100 ISO-K	750				VP-B38-210
		DN 160 ISO-K	750				VP-B38-216
		DN 63 ISO-K	1000				VP-B38-306
		DN 100 ISO-K	1000				VP-B38-310
		DN 160 ISO-K	1000				VP-B38-316
Bellow							
Stainless Steel							
		DN 63 ISO-K	130	14	7	90	VP-B39-006
		DN 100 ISO-K	130	14	7	128	VP-B39-010
		DN 160 ISO-K	150	16	8	175	VP-B39-016
		DN 200 ISO-K	230	20	10	235	VP-B39-020
		DN 250 ISO-K	250	20	10	285	VP-B39-025

		Nominal diameter	A	B	C	D	Order n°
Blanking flange							
		Stainless Steel					
		DN 63 ISO-F	130	12			VP-B40-006
		DN 100 ISO-F	165	12			VP-B40-010
		DN 160 ISO-F	225	16			VP-B40-016
		DN 200 ISO-F	285	16			VP-B40-020
		DN 250 ISO-F	335	16			VP-B40-025
		DN 320 ISO-F	425	20			VP-B40-032
		DN 400 ISO-F	510	20			VP-B40-040
	DN 500 ISO-F	610	20			VP-B40-050	
	DN 630 ISO-F	750	24			VP-B40-063	
Welding flange							
		Stainless Steel					
		DN 63 ISO-F	130	12	76,5	70	VP-B41-006
		DN 100 ISO-F	165	12	108,5	102	VP-B41-010
		DN 160 ISO-F	225	16	159,5	153	VP-B41-016
		DN 200 ISO-F	285	16	219,5	213	VP-B41-020
		DN 250 ISO-F	335	16	267,5	261	VP-B41-025
		DN 320 ISO-F	425	20	324,5	318	VP-B41-032
		DN 400 ISO-F	510	20	407	400	VP-B41-040
	DN 500 ISO-F	610	20	509	501	VP-B41-050	
	DN 630 ISO-F	750	24	661	651	VP-B41-063	
Flange with pipe							
		Stainless Steel					
		DN 63 ISO-F	100	76	70		VP-B42-006
		DN 100 ISO-F	100	108	102		VP-B42-010
		DN 160 ISO-F	100	159	153		VP-B42-016
		DN 200 ISO-F	100	219	213		VP-B42-020
		DN 250 ISO-F	100	267	261		VP-B42-025
		DN 320 ISO-F	100	324	318		VP-B42-032
		DN 400 ISO-F	100	408	400		VP-B42-040
	DN 500 ISO-F	100	508	500		VP-B42-050	
	DN 630 ISO-F	100	660	650		VP-B42-063	
Viewport							
		Plexiglass					
		DN 63 ISO-K	95	15			VP-B44-006
		DN 100 ISO-K	130	15			VP-B44-010
		DN 160 ISO-K	180	20			VP-B44-016
Protective cover							
		Plastic					
		DN 63 ISO-K				10	VP-B45-006
		DN 100 ISO-K				10	VP-B45-010
		DN 160 ISO-K				1	VP-B45-016
		DN 200 ISO-K				1	VP-B45-020
	DN 250 ISO-K				1	VP-B45-025	
			D = quantity delivered				



MATERIAL CONFLAT® CF

MATERIAL CONFLAT® CF

UHV Conflat® flange fittings

The CF sealing mechanism works from atmosphere to the lowest measurable pressures, within the temperature range -196°C. to 450°C. CF sealing mechanism is especially suited to condition requiring ultra-high vacuum, very clean environments, high temperatures or the containment of toxic, corrosive or radioactive gasses.

The seal is made by bolting tighter two identical flanges, which contains a knife-edge, with a flat metal ring gasket between the knife-edge (see the picture). The knife-edge is forced into the metal ring (usually copper). The knife edge press annular grooves in each side of the softer gasket material capable of withstanding high pressures or temperatures, fills the voids and defects in the knife edges producing an extremely reliable.

There are rotatable and fixed flanges. Rotatable flange is made from two pieces with the knife-edge part and external bolt holes being separate. Once the knife-edge part is welded in position it is easy to change the orientation of the bolt holes relative to the axis of the port.

This flange is used where alignment of a component to a chamber or to another component need to be set up accurately before the flange mounting bolts are tightened. Fixed flange is a single piece machined item with the bolt hole orientation fixed into position once they are welded.

Conflat® and equivalent flange names

While American manufacturers identify CF flanges using inch, the Europeans identify them with variety of conventions that can generate unpleasant misunderstand. They are many descriptions used to describe the same flange size as the flange OD in mm, the ID, in mm, of counterbore that accepts the tube for welding or the ID, in mm, of the largest clear bore.

Thus, the metric equivalent of a bored 23/4" OD CF flange could be called: CF70 indicating a 70 mm flange OD DN40CF indicating a 40 mm OD connecting tube or NW38CF indicating a 38,1 mm clear bore and 41,1 mm counterbore and CF23/4" is equivalent to FC70, DN40CF, NW38CF.




CF Flange name equivalent				OD (mm)		OD(in)
DN16CF	CF34	NW16CF	FC34	CF11/2"	34.00	1.33
DN40CF	CF70	NW40CF	FC70	CF23/4"	70.00	2.73
DN63CF	CF114	NW63CF	FC114	CF41/2"	114.00	4.47
DN100CF	CF150	NW100CF	FC150	CF6"	152.00	5.97
DN160CF	CF200	NW160CF	FC200	CF8"	202.00	7.97
DN200CF	CF250	NW200CF	FC250	CF10"	253.00	9.97
DN250CF	CF300	NW250CF	FC300	CF12"	306.00	13.25

Materials:

Our range of CF components is manufactured from selected high cleanliness AISI 316 stainless steel that offers optimum performances at an affordable cost AISI 316 LN stainless steel is also available on request for applications where harder material at higher bakeout temperature and lower magnetic permeability are required.




There are many types of CF gaskets.



Copper gasket	for general application. The most common is the high purity scratch, oxygen free, 1/4 hard copper gasket.
Silver plated copper gasket	protect against flaking oxide production caused by frequent high temperature bakeout
Fully annealed copper gasket	is used to minimize strain during bolt tightening
Aluminium gaskets	is used with aluminium knife-edge flange or with S.S. CF flange non submitted to high temperature bakeout
Viton gasket	re-usable elastomeric gasket used in non-UHV, non-bakeable applications
Gold-plated copper; silver diffused copper; zirconium-copper alloy; Wire of nickel, gold, lead, indium.	gaskets made for special application







- 1 Connection with screws
2 Connection with stud screws
3 Connection with DUO nuts


Nominal Diameter	A	O.D.	B	C	N. of Holes	Number of screws	Number of stud screws	Number of DUO nuts
DN 16 CF	34,0	1 1/3"	27,0	4,3	6	6xM4	6xM4	3xM4
DN 40 CF	69,5	2 3/4"	58,7	6,6	6	6xM6	6xM6	3xM6
DN 63 CF	113,5	4 1/2"	92,2	8,4	8	8xM8	8xM8	
DN 100 CF	152,0	6"	130,3	8,4	16	16xM8	16xM8	
DN 160 CF	202,5	8"	181,0	8,4	20	20xM8	20xM8	
DN 200 CF	253,0	10"	231,8	8,4	24	24xM8	24xM8	
DN 250 CF	306,0	12"	284,0	8,4	32	32xM8	32xM8	


		Nominal diameter	A	B	C	D	Order n°
Set of hexagonal bolts							
Stainless Steel							
		DN 16 CF	20	M4		25	VP-C01-001
		DN 40 CF	35	M6		25	VP-C01-004
		DN 63 CF	45	M8		25	VP-C01-006
		DN 100 CF	50	M8		25	VP-C01-010
		DN 160 CF	55	M8		25	VP-C01-016
		DN 200 CF	60	M8		25	VP-C01-020
		DN 250 CF	65	M8		25	VP-C01-025
		D = quantity delivered					
Set of hexagonal bolts for TAPPED hole							
Stainless Steel							
		DN 16 CF	16	M4		25	VP-C02-001
		DN 40 CF	25	M6		25	VP-C02-004
		DN 63 CF	30	M8		25	VP-C02-006
		DN 100 CF	35	M8		25	VP-C02-010
		DN 160 CF	40	M8		25	VP-C02-016
		DN 200 CF	45	M8		25	VP-C02-020
		DN 250 CF	50	M8		25	VP-C02-025
		D = quantity delivered					
Set of hexagonal bolts with DUO nuts							
Stainless Steel							
		DN 16 CF	20	M4		6+3	VP-C03-001
		DN 40 CF	35	M6		6+3	VP-C03-004
		DN 63 CF	40	M8		8+4	VP-C03-006
		DN 100 CF	45	M8		16+8	VP-C03-010
		DN 160 CF	50	M8		20+10	VP-C03-016
		DN 200 CF	55	M8		24+12	VP-C03-020
		DN 250 CF	60	M8		32+16	VP-C03-025
		D = quantity delivered					

		Nominal diameter	A	B	C	D	Order n°
Set of stud screws							
Stainless Steel							
		DN 16 CF	20	M4		25	VP-C04-001
		DN 40 CF	35	M6		25	VP-C04-004
		DN 63 CF	45	M8		25	VP-C04-006
		DN 100 CF	50	M8		25	VP-C04-010
		DN 160 CF	55	M8		25	VP-C04-016
		DN 200 CF	60	M8		25	VP-C04-020
		DN 250 CF	65	M8		25	VP-C04-025
		D = quantity delivered					
Gaskets							
Copper							
		DN 16 CF	2	21	16	10	VP-C05-001
		DN 40 CF	2	48	37	10	VP-C05-004
		DN 63 CF	2	82	63	10	VP-C05-006
		DN 100 CF	2	120	101	10	VP-C05-010
		DN 160 CF	2	171	152	10	VP-C05-016
		DN 200 CF	2	222	203	10	VP-C05-020
		DN 250 CF	2	273	258	5	VP-C05-025
		Annealed copper					
		DN 16 CF	2	21	16	5	VP-C05-101
		DN 40 CF	2	48	37	5	VP-C05-104
		DN 63 CF	2	82	63	5	VP-C05-106
		DN 100 CF	2	120	101	5	VP-C05-110
		DN 160 CF	2	171	152	5	VP-C05-116
		DN 200 CF	2	222	203	5	VP-C05-120
		DN 250 CF	2	273	258	5	VP-C05-125
Silver plated copper							
		DN 16 CF	2	21	16	5	VP-C05-201
		DN 40 CF	2	48	37	5	VP-C05-204
		DN 63 CF	2	82	63	5	VP-C05-206
		DN 100 CF	2	120	101	5	VP-C05-210
		DN 160 CF	2	171	152	5	VP-C05-216
		DN 200 CF	2	222	203	5	VP-C05-220
		DN 250 CF	2	273	258	5	VP-C05-225
Viton							
		DN 16 CF				5	VP-C05-501
		DN 40 CF				5	VP-C05-504
		DN 63 CF				1	VP-C05-506
		DN 100 CF				1	VP-C05-510
		DN 160 CF				1	VP-C05-516
		DN 200 CF				1	VP-C05-520
		DN 250 CF				1	VP-C05-525
			D = quantity delivered				

			Nominal diameter	A	B	C	D	Order n°
Blanking flange								
		AISI 316 L	1.4404	DN 16 CF	34	7,3		VP-C08-001
				DN 40 CF	69,5	12,7		VP-C08-004
				DN 63 CF	113,5	17,5		VP-C08-006
				DN 100 CF	152	20		VP-C08-010
				DN 160 CF	202,5	22		VP-C08-016
				DN 200 CF	253	24,5		VP-C08-020
				DN 250 CF	306	26		VP-C08-025
		AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	7,3	VP-C08-201
				DN 40 CF*	69,5	12,7		VP-C08-204
				DN 63 CF	113,5	17,5		VP-C08-206
				DN 100 CF	152	20		VP-C08-210
				DN 160 CF	202,5	22		VP-C08-216
				DN 200 CF	253	24,5		VP-C08-220
				DN 250 CF	306	26		VP-C08-225
Blanking flange with tapped holes								
		AISI 316 L	1.4404	DN 16 CF	34	7,3		VP-C08-501
				DN 40 CF	69,5	12,7		VP-C08-504
				DN 63 CF	113,5	17,5		VP-C08-506
				DN 100 CF	152	20		VP-C08-510
				DN 160 CF	202,5	22		VP-C08-516
				DN 200 CF	253	24,5		VP-C08-520
				DN 250 CF	306	26		VP-C08-525
		AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	7,3	VP-C08-701
				DN 40 CF*	69,5	12,7		VP-C08-704
				DN 63 CF	113,5	17,5		VP-C08-706
				DN 100 CF	152	20		VP-C08-710
				DN 160 CF	202,5	22		VP-C08-716
				DN 200 CF	253	24,5		VP-C08-720
				DN 250 CF	306	26		VP-C08-725
* not forged								

			Nominal diameter	A	B	C	D	Order n°
Blanking flange rotatable								
AISI 316 L	1.4404		DN 16 CF	34	7,3	19,4	5,8	VP-C09-001
			DN 40 CF	69,5	12,7	40,5	7,6	VP-C09-004
			DN 63 CF	113,5	19	70,5	12,6	VP-C09-006
			DN 100 CF	152	21,5	109	14,3	VP-C09-010
			DN 160 CF	202,5	24	160	15,8	VP-C09-016
			DN 200 CF	253	24,5	207	17,1	VP-C09-020
			DN 250 CF	306	26	257	18	VP-C09-025
AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	7,3	19,4	5,8	VP-C09-201
			DN 40 CF*	69,5	12,7	40,5	7,6	VP-C09-204
			DN 63 CF	113,5	19	70,5	12,6	VP-C09-206
			DN 100 CF	152	21,5	109	14,3	VP-C09-210
			DN 160 CF	202,5	24	160	15,8	VP-C09-216
			DN 200 CF	253	24,5	207	17,1	VP-C09-220
			DN 250 CF	306	26	257	18	VP-C09-225
			* not forged					
Blanking flange rotatable with tapped holes								
AISI 316 L	1.4404		DN 16 CF	34	7,3	19,4	5,8	VP-C09-501
			DN 40 CF	69,5	12,7	40,5	7,6	VP-C09-504
			DN 63 CF	113,5	19	70,5	12,6	VP-C09-506
			DN 100 CF	152	21,5	109	14,3	VP-C09-510
			DN 160 CF	202,5	24	160	15,8	VP-C09-516
			DN 200 CF	253	24,5	207	17,1	VP-C09-520
			DN 250 CF	306	26	257	18	VP-C09-525
AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	7,3	19,4	5,8	VP-C09-701
			DN 40 CF*	69,5	12,7	40,5	7,6	VP-C09-704
			DN 63 CF	113,5	19	70,5	12,6	VP-C09-706
			DN 100 CF	152	21,5	109	14,3	VP-C09-710
			DN 160 CF	202,5	24	160	15,8	VP-C09-716
			DN 200 CF	253	24,5	207	17,1	VP-C09-720
			DN 250 CF	306	26	257	18	VP-C09-725
			* not forged					

			Nominal diameter	A	B	C	D	Order n°
Welding flange								
AISI 316 L	1.4404		DN 16 CF	34	14,2	19,2	16	VP-C10-001W
			DN 16 CF	34	7,3	19,2	16	VP-C10-001
			DN 40 CF	69,5	12,7	40,2	37	VP-C10-004
			DN 63 CF	113,5	17,5	70,2	64	VP-C10-006
			DN 100 CF	152	20	108,5	102	VP-C10-010
			DN 160 CF	202,5	22	159,5	153	VP-C10-016
			DN 200 CF	253	24,5	206,5	200	VP-C10-020
			DN 250 CF	306	26	256,5	250	VP-C10-025
			(W) long flange					
AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	14,2	19,2	16	VP-C10-201W
			DN 16 CF*	34	7,3	19,2	16	VP-C10-201
			DN 40 CF*	69,5	12,7	40,2	37	VP-C10-204
			DN 63 CF	113,5	17,5	70,2	64	VP-C10-206
			DN 100 CF	152	20	108,5	102	VP-C10-210
			DN 160 CF	202,5	22	159,5	153	VP-C10-216
			DN 200 CF	253	24,5	206,5	200	VP-C10-220
			DN 250 CF	306	26	256,5	250	VP-C10-225
			* not forged					

Welding flange with tapped holes										
AISI 316 L	1.4404		DN 16 CF	34	7,3	19,2	16	VP-C10-501		
	DN 40 CF		69,5	12,7	40,2	37	VP-C10-504			
	DN 63 CF		113,5	17,5	70,2	64	VP-C10-506			
	DN 100 CF		152	20	108,5	102	VP-C10-510			
	DN 160 CF		202,5	22	159,5	153	VP-C10-516			
	DN 200 CF		253	24,5	206,5	200	VP-C10-520			
	DN 250 CF		306	26	256,5	250	VP-C10-525			
AISI 316 LN	ESR-FORG	1.4429	DN 16 CF*	34	7,3	19,2	16	VP-C10-701		
			DN 40 CF*	69,5	12,7	40,2	37	VP-C10-704		
			DN 63 CF	113,5	17,5	70,2	64	VP-C10-706		
			DN 100 CF	152	20	108,5	102	VP-C10-710		
			DN 160 CF	202,5	22	159,5	153	VP-C10-716		
			DN 200 CF	253	24,5	206,5	200	VP-C10-720		
			DN 250 CF	306	26	256,5	250	VP-C10-725		
				* not forged						